

Express Mail Label No.

EJ 108 877 803 US

Date of Mailing NOVEMBER 29, 2001

PATENT  
Case No. **DP-306477**  
(7500/124)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE  
APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTOR(S):           SANJIV G. TEWANI  
                              MARK W. LONG  
                              MARK O. BODIE  
                              JAMES P. HAMBERG

TITLE:                   POWERTRAIN MOUNT WITH  
                              FLOATING TRACK

ATTORNEYS:            SCOTT A. MCBAIN, ESQ.  
                              DELPHI TECHNOLOGIES, INC.  
                              LEGAL STAFF  
                              P.O. BOX 5052  
                              MAIL CODE: 480-414-420  
                              TROY, MICHIGAN 48007-5052  
                              (248) 267-5514

DP-306477

## POWERTRAIN MOUNT WITH FLOATING TRACK

5

### TECHNICAL FIELD OF THE INVENTION

The present invention relates to powertrain mounts for motor vehicles, and more particularly to a powertrain mount with a floating orifice track.

10

### BACKGROUND OF THE INVENTION

It is desirable to provide motor vehicles with improved operating smoothness by damping and/or isolating powertrain vibrations of the vehicle. A variety of mount assemblies are presently available to inhibit such engine and transmission vibrations. Hydraulic mount assemblies of this type typically include a reinforced, hollow rubber body that is closed by a resilient diaphragm so as to form a cavity. This cavity is separated into two chambers by a plate. A first or primary chamber is formed between the partition plate and the body, and a secondary chamber is formed between the plate and the diaphragm.

15

20

25

The chambers may be in fluid communication through a relatively large central passage in the plate, and a decoupler may be positioned in the central passage of the plate to reciprocate in response to the vibrations. The decoupler movement alone accommodates small volume changes in the two chambers. When, for example, the decoupler moves in a direction toward the diaphragm, the volume of the portion of the decoupler cavity in the primary chamber increases and the volume of the portion in the secondary chamber correspondingly decreases, and vice-versa. In this way, for certain small vibratory amplitudes and generally higher frequencies, fluid flow between the chambers is substantially avoided and undesirable hydraulic damping is eliminated. In effect, the decoupler is a passive tuning device.

As an alternative or in addition to the relatively large central passage, an orifice track is normally provided. The orifice track has a relatively small, restricted flow passage extending around the perimeter of the orifice plate. Each end of the track has an opening, with one opening communicating with the primary chamber and the other with the secondary chamber. The orifice track provides the hydraulic mount assembly with another passive tuning component, and when combined with the decoupler, provides at least three distinct dynamic operating modes. The particular operating mode is primarily determined by the flow of fluid between the two chambers. More specifically, small amplitude vibrating input, such as from relatively smooth engine idling or the like, produces no damping due to the action of the decoupler, as explained above. In contrast, large amplitude vibrating inputs, such as large suspension inputs, produce high velocity fluid flow through the orifice track, and an accordingly high level of damping force and desirable control and smoothing action. A third or intermediate operational mode of the mount occurs during medium amplitude inputs experienced in normal driving and resulting in lower velocity fluid flow through the orifice track. In response to the decoupler switching from movement in one direction to another in each of the modes, a limited amount of fluid can bypass the orifice track by moving around the edges of the decoupler, smoothing the transition.

Passive hydraulic mounts are tuned to provide damping in a pre-determined frequency range which is typically in the range of about 10-15 Hz. Due to the generation of damping, the dynamic stiffness of the mount is increased significantly. An increase in dynamic stiffness is not desirable from the isolation point of view.

## SUMMARY OF THE INVENTION

The present invention is a powertrain mount comprising an orifice plate and a slug. The orifice plate defines an orifice track having a first cross-sectional area, and the slug is disposed in the orifice track. The slug has a bore with a second cross-sectional area less than the first cross-sectional area.

Accordingly, it is an object of the present invention to provide an improved powertrain mount of the type described above with a relatively low dynamic stiffness at a disturbance frequency such as engine idle or some other predetermined mode of operation of the engine.

Another object of the present invention is to provide an improved powertrain mount of the type described above including a slug which floats in the orifice track.

The foregoing and other features and advantages of the invention will become further apparent from the following detailed description of the presently preferred embodiments, read in conjunction with the accompanying drawings. The detailed description and drawings are merely illustrative of the invention rather than limiting, the scope of the invention being defined by the appended claims and equivalents thereof.

## BRIEF DESCRIPTION OF THE DRAWINGS

**FIG. 1** is a cross-sectional view of a powertrain mount according to the present invention for a motor vehicle; and

**FIG. 2** is a cross-sectional view of a portion of the powertrain mount taken along line 2-2 in **FIG. 1**.

## DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENTS

**FIGS. 1 and 2** show an improved hydraulic mount assembly **10** according to the present invention. The mount assembly **10** is particularly adapted for mounting an internal combustion engine and/or transmission to a frame in a motor vehicle. The mount assembly **10** includes a metal base plate **16** and a molded body **18**. The molded body **18** has an elastomeric portion molded around a metal substrate, and includes a plurality of studs **20** projecting outwardly to attach the molded body to the engine or transmission. The base plate **16** is similarly equipped with a plurality of outwardly projecting studs **22** to attach the base plate to the frame.

The base plate **16** and the molded body **18** are configured to be joined to form a hollow cavity for receiving a damping liquid, such as a glycol fluid. An elastomeric diaphragm **24** of natural or synthetic rubber is attached around its perimeter to the base plate **16** and/or to the body **18**, and extends across the cavity. The diaphragm **24** may include an annular rim section having a radially inwardly facing internal groove formed between upper and lower shoulders such as is described in U.S. Patent No. 5,263,693, the disclosure of which is hereby incorporated by reference. The shoulders are normally flexible so as to sealingly receive the periphery of a die-cast metal or plastic partition plate **28**.

The partition plate **28** spans the cavity to define a primary chamber **30** and a secondary chamber **32**. With a containment plate **34**, the partition plate **28** defines an orifice track **36**. The orifice track permits the flow of fluid between the primary chamber **30** and the secondary chamber **32**, as is well known. To this end, an entrance **38** is provided in the orifice plate **28**, and an exit **40** is provided in the containment plate **34**.

A floating orifice track or slug **42** is disposed in the orifice track **36**. The slug **42** has an outside dimension closely sized to the inside dimension of the orifice track, and is movable along a portion of the orifice track. The slug **42** also has a bore **43** which may have either a constant or a varying cross-sectional area. In either event, the effective cross-sectional area of the bore **43** is less than the cross-sectional area of the orifice track **36**.

To limit the movement of the slug, mechanical stops **44** and **46** may be provided in addition to the usual bends in the orifice track. The length of free travel of the slug **42** is chosen such that its movement is not restricted during small amplitude input displacements to the mount. In this case, the relatively large cross-sectional area of the orifice track **36** primarily influences the flow characteristics of the fluid. The track is designed such that the fluid in the track goes into resonance at the frequency where a low dynamic stiffness is desired. The force associated with the fluid flow therefore attempts to cancel the force associated with the static stiffness of the mount. For large input displacements, the slug **42** reaches the limits of the free space. When the slug **42** is at one of its limits, the flow of the fluid is primarily influenced by the smaller cross-sectional area of the bore **43**.

The hydraulic mount **10** is designed such that during engine idle conditions, the mount generates a dynamic stiffness much lower than its static stiffness at a frequency related to engine idle RPM. Based on the application, the mount may likewise be tuned to provide a low dynamic stiffness at a different frequency. At the same time the hydraulic mount generates damping for large road inputs, and as a result higher dynamic stiffness to control the powertrain. For a typical four cylinder engine, isolation during engine idle conditions requires the mount to generate a low dynamic stiffness at around 20 Hz. For control during large road inputs, the powertrain mount **10** generates damping and large dynamic stiffness in the frequency range of about 10-15 Hz.

While the embodiment of the invention disclosed herein is presently considered to be preferred, various changes and modifications can be made without departing from the spirit and scope of the invention. The scope of the invention is indicated in the  
5 appended claims, and all changes that come within the meaning and range of equivalents are embraced therein.